

Description

SMA connectors are precision connectors for microwave applications up to 18 GHz. The extended frequency version operates with excellent return loss performances up to 26.5 GHz. There is a huge variety of applications for SMA connectors, as in telecom, test & measurement, instruments, avionics, etc.

11911014 -- RF CONNECTOR - 50OHMS , RP SMA MALE , STRAIGHT , CRIMP TYPE , RG316 , RG174 , RG188 , LMR100 CABLE

PART CODE: 11911014

| | |
|---------------------------|---------------|
| Type | RF Connector |
| Gender | Plug (Male) |
| Orientation | Straight |
| Termination Style | Cable – Crimp |
| Impedance (Ohms) | 50 |
| Body Finish | Gold |
| Body Material | Brass |
| Contact Finish | Gold |
| Contact Material | Brass |
| Contact Termination Style | Solder |
| Insulator Material | PTFE |
| Cable Type | RG316 |
| Coupling Mechanism | Threaded |
| Mounting Feature | |
| Max Frequency (GHz) | 18 |
| Polarity | Reverse |
| Thread Direction | Standard |
| Min. Temp. (Celsius) | -65 |
| Max. Temp. (Celsius) | 165 |



VINSURWAVES

Address: C-211, First Block, KSSIDC Complex, Near Software Technology Park of India, Electronics City Phase-1, Bengaluru - 560100, Karnataka, INDIA, Phone: 080-28520115, Mob: +91- 9886991616, E-mail: info@vinsurwaves.com | Website: www.vinsurwaves.com.