

Description

SMB (Sub Miniature version B) connectors are coaxial RF Connectors. The SMB interface features a snap-on coupling mechanism and is available in 50 Ohm and 75 Ohm configurations. SMB connectors conform to the requirements of MIL-C-39012, and the interface is in compliance with MIL-STD-348. SMB connectors offer broadband performance with low reflection DC to 4 GHz and utilize die cast components on non-critical areas to provide a low-cost solution.

11611015 -- RF CONNECTOR - 50OHMS , SMB MALE , STRAIGHT , CRIMP TYPE , RG58 , RG142 , LMR195 CABLE

PART CODE: 11611015

Type	RF Connector
Gender	Plug (Male)
Orientation	Straight
Termination Style	Cable - Crimp
Impedance (Ohms)	50
Body Finish	Gold
Body Material	Brass
Contact Finish	Gold
Contact Material	Brass
Contact Termination Style	Solder
Insulator Material	PTFE
Cable Type	RG58
Coupling Mechanism	Push-on
Mounting Feature	
Max Frequency (GHz)	4
Polarity	Standard
Min. Temp. (Celsius)	-65
Max. Temp. (Celsius)	165



VINSURWAVES

Address: C-211, First Block, KSSIDC Complex, Near Software Technology Park of India, Electronics City Phase-1, Bengaluru - 560100, Karnataka, INDIA, Phone: 080-28520115, Mob: +91- 9886991616, E-mail: info@vinsurwaves.com | Website: www.vinsurwaves.com.